





CompSci 275, CONSTRAINT Networks

Rina Dechter, Winter 2026

General Search Strategies: Look-ahead
Chapter 5

Directional i-Consistency



Adaptive

d-path

d-arc

E: $E \neq D, E \neq C, E \neq B$

D: $D \neq C, D \neq A$

C: $C \neq B$

B: $A \neq B$

A:

R_{DCB}

R_{DC}, R_{DB}
 R_{CB}

R_D
 R_C
 R_D

Outline (Chapter 5)

- The search tree for CSPs, Variable ordering and consistency level
- Look-ahead for value selection:
 - Forward checking,
 - Full-arc-consistency,
 - partial look-ahead,
 - maintaining arc-consistency
- Dynamic Variable ordering (DVO, DVFC)
- Search for Satisfiability
- Converting a CSP into a SAT problem

What if the constraint network is not backtrack-free?


- Backtrack-free in general is too costly, so what to do?
- Search?
- What is the search space?
- How to search it? Breadth-first? Depth-first?

The search space for a CN

- A tree of all partial solutions
- A partial solution: (a_1, \dots, a_j) satisfying all relevant constraints
- The size of the underlying search space depends on:
 - Variable ordering
 - Level of consistency possessed by the problem

Search spaces: the effect of ordering


Z divides, X,Y,L



States = partial solutions


Operators: next consistent value

Goal: consistent solutions



Ordering d1 = (z,x,y,l): 1 deadend

Ordering d2 = (x,y,l,z): 18 deadends



Search spaces: the effect of consistency level

- After arc-consistency $z=5$ and $l=5$ are removed

Ordering $d1 = (z,x,y,l)$: 1 deadend
 Ordering $d2 = (x,y,l,z)$: 18 deadends

- After path-consistency

$$R'_{zx} = \{(2, 2), (2, 4), (3, 3)\}$$




$$R'_{zy} = \{(2, 2), (2, 4), (3, 3)\}$$

$$R'_{zl} = \{(2, 2), (2, 6), (3, 6)\}$$

$$R'_{xy} = \{(2, 2), (2, 4), (4, 2), (4, 4), (3, 3)\}$$

$$R'_{xl} = \{(2, 2), (2, 6), (4, 2), (4, 6), (3, 6)\}$$

$$R'_{yl} = \{(2, 2), (2, 6), (4, 2), (4, 6), (3, 6)\}.$$



The effect of consistency level on search

Theorem 5.1.3 *Let \mathcal{R}' be a tighter network than \mathcal{R} , where both represent the same set of solutions. For any ordering d , any path appearing in the search graph derived from \mathcal{R}' also appears in the search graph derived from \mathcal{R} . \square*

Cost of node's expansion;

More constraints require more consistency checks

- Number of consistency checks for toy problem:
 - For d1: 19 for R (original), 43 for R' (after path consistency)
 - For d2: 91 on R and 56 on R'
- Reminder:



Definition 5.1.5 (backtrack-free network) *A network R is said to be backtrack-free along ordering d if every leaf node in the corresponding search graph is a solution.*

Backtracking search for a solution


2 search spaces:

$d1 = (x1, x2, x3, x4, x5, x6, x7)$

$d2 = (x1, x7, x4, x5, x6, x3, x2)$





(a)




(b)

Backtracking Search for a single Solution





(a)




(b)

Backtracking search for *all* solutions




(a)




(b)


Backtracking search for *all* solutions



For all tasks
 Time: $O(\exp(n))$
 Space: linear




(a)




(b)


Traversing breadth-first (BFS)?



**BFS space is $\exp(n)$ while no
Time gain \rightarrow use DFS**



(a)



(b)

Backtracking

```
procedure BACKTRACKING
Input: A constraint network  $P = (X, D, C)$ .
Output: Either a solution, or notification that the network is inconsistent.

 $i \leftarrow 1$            (initialize variable counter)
 $D'_i \leftarrow D_i$    (copy domain)
while  $1 \leq i \leq n$ 
  instantiate  $x_i \leftarrow \text{SELECTVALUE}$ 
  if  $x_i$  is null      (no value was returned)
     $i \leftarrow i - 1$  (backtrack)
  else
     $i \leftarrow i + 1$  (step forward)
     $D'_i \leftarrow D_i$ 
end while
if  $i = 0$ 
  return "inconsistent"
else
  return instantiated values of  $\{x_1, \dots, x_n\}$ 
end procedure

subprocedure SELECTVALUE (return a value in  $D'_i$  consistent with  $\vec{a}_{i-1}$ )

  while  $D'_i$  is not empty
    select an arbitrary element  $a \in D'_i$ , and remove  $a$  from  $D'_i$ 
    if CONSISTENT( $\vec{a}_{i-1}, x_i = a$ )
      return  $a$ 
  end while
  return null           (no consistent value)
end procedure
```

Figure 5.4: The backtracking algorithm.


- Complexity of extending a partial solution:
 - Complexity of *consistent* $O(e \log t)$, t bounds tuples, e , constraints
 - Complexity of *selectValue* $O(e k \log t)$

Improving backtracking

- Before search: (reducing the search space)
 - Arc-consistency, path-consistency
 - Variable ordering (fixed)
- During search:
 - Look-ahead schemes:
 - value ordering,
 - variable ordering (if not fixed)
 - Look-back schemes:
 - Backjump
 - Constraint recording
 - Dependency-directed backtracking

Look-ahead: value orderings

- Intuition:
 - Choose value least likely to yield a dead-end
 - Approach: apply constraint propagation at each node in the search tree
- Forward-checking
 - (check each unassigned variable separately)
- Maintaining arc-consistency (MAC)
 - (apply full arc-consistency)
- Full look-ahead
 - One pass of arc-consistency (AC-1)
- Partial look-ahead
 - directional-arc-consistency



Generalized look-ahead

```
procedure GENERALIZED-LOOKAHEAD
Input: A constraint network  $P = (X, D, C)$ 
Output: Either a solution, or notification that the network is inconsis-
tent.



 $D'_i \leftarrow D_i$  for  $1 \leq i \leq n$     (copy all domains)
 $i \leftarrow 1$                         (initialize variable counter)
while  $1 \leq i \leq n$ 
    instantiate  $x_i \leftarrow \text{SELECTVALUE-XXX}$ 
    if  $x_i$  is null                        (no value was returned)
         $i \leftarrow i - 1$                 (backtrack)
        reset each  $D'_k, k > i$ , to its value before  $x_i$  was last instantiated
    else
         $i \leftarrow i + 1$                 (step forward)
end while
if  $i = 0$ 
    return "inconsistent"
else
    return instantiated values of  $\{x_1, \dots, x_n\}$ 
end procedure
```

Figure 5.7: A common framework for several look-ahead based search algorithms. By replacing SELECTVALUE-XXX with SELECTVALUE-FORWARD-CHECKING, the forward checking algorithm is obtained. Similarly, using SELECTVALUE-ARC-CONSISTENCY yields an algorithm that interweaves arc-consistency and search.


Forward-checking for value rejection

Forward-checking

(check each unassigned variable separately)




Forward-checking for value rejection



FC overhead: $O(ek^2)$

- For each value of a future variable x_u : e_u
- Tests: $O(k e_u)$, for all future variables $O(ke)$
- For all current domain $O(k^2 e)$





Forward-checking

```
procedure SELECTVALUE-FORWARD-CHECKING
  while  $D'_i$  is not empty
    select an arbitrary element  $a \in D'_i$ , and remove  $a$  from  $D'_i$ 
    empty-domain  $\leftarrow$  false
    for all  $k, i < k \leq n$ 
      for all values  $b$  in  $D'_k$ 
        if not CONSISTENT( $\vec{a}_{i-1}, x_i = a, x_k = b$ )
          remove  $b$  from  $D'_k$ 
        end for
      if  $D'_k$  is empty      ( $x_i = a$  leads to a dead-end)
        empty-domain  $\leftarrow$  true
      if empty-domain    (don't select  $a$ )
        reset each  $D'_k, i < k \leq n$  to value before  $a$  was selected
      else
        return  $a$ 
    end while
  return null              (no consistent value)
end procedure
```

Figure 5.8: The SELECTVALUE subprocedure for the forward checking algorithm.

Complexity of selectValue-forward-checking at each node: $O(ek^2)$

Example: two not touch



Arc-consistency look-ahead

(Gacshnig, 1977)

- Applies full arc-consistency on all un-instantiated variables following each candidate value assignment to the current variable.
- Complexity:
 - If optimal arc-consistency is used: $O(ek^3)$
 - What is the complexity overhead when AC-1 is used at each node?

Forward-checking: $O(ek^2)$

Full arc-consistency look-ahead
With optimal AC: $O(ek^3)$

MAC: Maintaining arc-consistency (Sabin and Freuder 1994)

- Perform arc-consistency in a binary search tree: Given a domain $X=\{1,2,3,4\}$ the algorithm assigns $X=1$ (and apply arc-consistency) and if $x=1$ is pruned, it applies arc-consistency to $X=\{2,3,4\}$
- If inconsistency is not discovered, a new variable is selected (not necessarily X)



Arc-consistency look-ahead:

```
subprocedure SELECTVALUE-ARC-CONSISTENCY

  while  $D'_i$  is not empty
    select an arbitrary element  $a \in D'_i$ , and remove  $a$  from  $D'_i$ 
    repeat
      removed-value  $\leftarrow$  false
      for all  $j, i < j \leq n$ 
        for all  $k, i < k \leq n$ 
          for each value  $b$  in  $D'_j$ 
            if there is no value  $c \in D'_k$  such that
              CONSISTENT( $\vec{a}_{i-1}, x_i = a, x_j = b, x_k = c$ )
                remove  $b$  from  $D'_j$ 
                removed-value  $\leftarrow$  true
            end for
          end for
        end for
      end for
    until removed-value = false
    if any future domain is empty (don't select  $a$ )
      reset each  $D'_j, i < j \leq n$ , to value before  $a$  was selected
    else
      return  $a$ 
    end while
  return null (no consistent value)
end procedure
```

Figure 5.10: The SELECTVALUE subprocedure for arc-consistency, based on the AC-1 algorithm.

AC for value rejection




FW overhead: $O(ek^2)$

MAC overhead: $O(ek^3)$


AC for value rejection

Arc-consistency prunes $x_1 = \text{red}$
Prunes the whole tree



FW overhead: $O(ek^2)$

MAC overhead: $O(ek^3)$





Full and partial look-ahead

- Full looking ahead:
 - Make one pass through future variables (delete, repeat-until)
- Partial look-ahead:
 - Applies (similar-to) directional arc-consistency to future variables.
 - Complexity: also $O(ek^3)$
 - More efficient than MAC

Example of partial look-ahead

Example 5.3.3 Consider the problem in Figure 5.3 using the same ordering of variables and values as in Figure 5.9. Partial-look-ahead starts by considering $x_1 = red$. Applying directional arc-consistency from x_1 towards x_7 will first shrink the domains of x_3 , x_4 and x_7 , (when processing x_1), as was the case for forward-checking. Later, when directional arc-consistency processes x_4 (with its only value, “blue”) against x_7 (with its only value, “blue”), the domain of x_4 will become empty, and the value “red” for x_1 will be rejected. Likewise, the value $x_1 = blue$ will be rejected. Therefore, the whole tree in Figure 5.9 will not be visited if either partial-look-ahead or the more extensive look-ahead schemes are used. With this level of look-ahead only the subtree below $x_1 = green$ will be expanded.

□



1/26/2026

Branching-ahead: dynamic value ordering


Rank order the promise in non-rejected values to estimate the likelihood of leading to a solution.

- Rank functions
 - MC (min conflict) counts the number of conflicts with each future domain that are otherwise consistent.
 - MD (min domain) score is the largest domain size of future variables.
 - ES (expected solution counts)
- MC results (Frost and Dechter, 1996)
- ES – showed good performance using IJGP (Kask, Dechter and Gogate, 2004)

Dynamic variable ordering (DVO)


- Following constraint propagation, choose the most constrained variable
- **Intuition:** early discovery of dead-ends
- **Highly effective:** the single most important heuristic to cut down search space
- Most popular with FC
- Dynamic search rearrangement (Bitner and Reingold, 1975) (Purdon,1983)

Forward-checking: variable ordering




FW overhead: $O(ek^2)$

MAC overhead: $O(ek^3)$




Forward-checking: variable ordering

After $X_1 = \text{red}$ choose X_3 and not X_2





FW overhead: $O(ek^2)$

MAC overhead: $O(ek^3)$



Forward-checking: variable ordering

After $X_1 = \text{red}$ choose X_3 and not X_2




FW overhead: $O(ek^2)$

MAC overhead: $O(ek^3)$


Forward-checking: variable ordering

After $X_1 = \text{red}$ choose X_3 and not X_2




FW overhead: $O(ek^2)$

MAC overhead: $O(ek^3)$



Example: DVO with forward-checking (DVFC)



Example 5.3.4 Consider again the example in Figure 5.3. Initially, all variables have domain size of 2 or more. DVFC picks x_7 , whose domain size is 2, and the value $\langle x_7, blue \rangle$. Forward-checking propagation of this choice to each future variable restricts the domains of x_3 , x_4 and x_5 to single values, and reduces the size of x_1 's domain by one. DVFC selects x_3 and assigns it its only possible value, *red*. Subsequently, forward-checking causes variable x_1 to also have a singleton domain. The algorithm chooses x_1 and its only consistent value, *green*. After propagating this choice, we see that x_4 has one value, *red*; it is selected and assigned the value. Then x_2 can be selected and assigned its only consistent value, *blue*. Propagating this assignment does not further shrink any future domain. Next, x_5 can be selected and assigned *green*. The solution is then completed, without dead-ends, by assigning *red* or *teal* to x_6 . \square

Algorithm DVO (DVFC)

```
procedure DVFC
Input: A constraint network  $\mathcal{R} = (X, D, C)$ 
Output: Either a solution, or notification that the network is inconsistent.
   $D'_i \leftarrow D_i$  for  $1 \leq i \leq n$     (copy all domains)
   $i \leftarrow 1$                           (initialize variable counter)
   $s = \min_{i < j \leq n} |D'_j|$  (find future var with smallest domain)
   $x_{i+1} \leftarrow x_s$  (rearrange variables so that  $x_s$  follows  $x_i$ )
  while  $1 \leq i \leq n$ 
    instantiate  $x_i \leftarrow \text{SELECTVALUE-FORWARD-CHECKING}$ 
    if  $x_i$  is null (no value was returned)
      reset each  $D'$  set to its value before  $x_i$  was last instantiated
       $i \leftarrow i - 1$  (backtrack)
    else
      if  $i < n$ 
         $i \leftarrow i + 1$  (step forward to  $x_s$ )
         $s = \min_{i < j \leq n} |D'_j|$  (find future var with smallest domain)
         $x_{i+1} \leftarrow x_s$  (rearrange variables so that  $x_s$  follows  $x_i$ )
         $i \leftarrow i + 1$  (step forward to  $x_s$ )
  end while
  if  $i = 0$ 
    return "inconsistent"
  else
    return instantiated values of  $\{x_1, \dots, x_n\}$ 
end procedure
```

Figure 5.12: The DVFC algorithm. It uses the SELECTVALUE-FORWARD-CHECKING sub-procedure given in Fig. 5.8.

DVO: Dynamic variable ordering, more involved heuristics

- *dom*: choose a variable with min domain
- *deg*: choose variable with max degree
- *dom+deg*: dom and break ties with max degree
- *dom/deg* (Bessiere and Ragin, 96): choose min dom/deg
- *dom/wdeg*: domain divided by weighted degree. Constraints are weighted as they get involved in more conflicts. wdeg: sum the weights of all constraints that touch x.

Implementing look-aheads

- Cost of node generation should be reduced
- Solution: keep a table of viable domains for each variable and each level in the tree.
- Space complexity $O(n^2k)$
- Node generation = table updating $O(e_d k) \Rightarrow O(ek)$

Outline



- The search tree for CSPs, Variable ordering and consistency level
- Look-ahead for value selection:
 - Forward checking,
 - Full-arc-consistency,
 - partial look-ahead,
 - maintaining arc-consistency
- Dynamic Variable ordering (DVO, DVFC)
- Search for Satisfiability
- Converting a CSP into a SAT problem

Branching strategies (selecting the search space)


(see vanBeek, chapter 4 in Handbook)

- Enumeration branching: the naïve backtracking search choice
- A branching strategy in the search tree: a set of branching constraints $p(b_1, \dots, b_j)$ where b_i is a branching constraint
- Branches are often ordered using a heuristic.
- To ensure completeness, the constraints that are ordered on the branches should be exclusive and exhaustive.
- Most common are unary constraints:
 - Enumeration: $(x=1, x=2, x=3 \dots)$
 - Binary choices: $(x=1, x \neq 1)$
 - Domain splitting: $(x > 3, x < 3)$
- Using domain-specific formulas
 - Scheduling: one job before or after: $(x_1 + d_1 < x_2, x_2 + d_2 < x_1)$
 - Can be simulated by auxiliary variables.
 - Searching the dual problem
 - Formula-based splitting in SAT



Branching on the dual graph



Primal graph



Dual graph



Randomization

- Randomized variable selection (for tie breaking rule)
- Randomized value selection (for tie breaking rule)
- Random restarts with increasing time-cutoff
- Capitalizing on huge performance variance
- All modern SAT solvers that are competitive use restarts.

The cycle-cutset effect

(relationship of look-ahead to some graph structure)

- A cycle-cutset is a subset of nodes in an undirected graph whose removal results in a graph with no cycles
- A constraint problem whose graph has a cycle-cutset of size c can be solved by partial look-ahead in time $O((n - c)k^{(c+2)})$
- Question: what is the size of the search space when the cycle-cutset has size: 1 (cycle), 2, 5...

Extensions to stronger look-ahead

- Extend to path-consistency or i-consistency or generalized-arc-consistency

Definition 5.3.7 (general arc-consistency) *Given a constraint $C = (R, S)$ and a variable $x \in S$, a value $a \in D_x$ is supported in C if there is a tuple $t \in R$ such that $t[x] = a$. t is then called a support for $\langle x, a \rangle$ in C . C is arc-consistent if for each variable x , in its scope and each of its values, $a \in D_x$, $\langle x, a \rangle$ has a support in C . A CSP is arc-consistent if each of its constraints is arc-consistent.*

Search for SAT

What is SAT?

Given a sentence:

- **Sentence:** conjunction of clauses

$$(c_1 \vee \neg c_4 \vee c_5 \vee c_6) \wedge (c_2 \vee \neg c_3) \wedge (\neg c_4)$$

- **Clause:** disjunction of literals $(c_2 \vee \neg c_3)$

- **Literal:** a term or its negation $c_1, \neg c_6$

- **Term:** Boolean variable $c_1 = 1 \Leftrightarrow \neg c_1 = 0$

Question: Find an assignment of truth values to the Boolean variables such the sentence is satisfied.

SAT (continued)

from Darwiche chapter 3

- Representation:

$$(A \vee B \vee \neg C) \wedge (\neg A \vee D) \wedge (B \vee C \vee D)$$

A convenient way to notate sentences in CNF is using sets. Specifically, a clause $l_1 \vee l_2 \vee \dots \vee l_m$ is expressed as a set of literals $\{l_1, l_2, \dots, l_m\}$. Moreover, a conjunctive normal form $\alpha_1 \wedge \alpha_2 \wedge \dots \wedge \alpha_n$ is expressed as a set of clauses $\{\alpha_1, \alpha_2, \dots, \alpha_n\}$. For example, the CNF given above would be expressed as:

$$\{ \{A, B, \neg C\}, \{\neg A, D\}, \{B, C, D\} \}.$$

Resolution

1. $\{\neg P, R\}$
 2. $\{\neg Q, R\}$
 3. $\{\neg R\}$
 4. $\{P, Q\}$
-

- 1: $(P \rightarrow R)$
- 2: $(Q \rightarrow R)$
- 4: $(\sim P \rightarrow Q)$

5. $\{\neg P\}$ 1, 3
6. $\{\neg Q\}$ 2, 3
7. $\{Q\}$ 4, 5
8. $\{\}$ 6, 7

The clauses before the line represent initial clauses, while clauses below the line represent resolvents, together with the identifiers of clauses used to obtain them. The above resolution trace shows that we can derive the empty clause from the initial set of Clauses (1–4). Hence, the original clauses, together, are unsatisfiable.

DP (Davis Putnam) or directional resolution (Dechter and Rish, 1994)

The DP algorithm, also known as *directional resolution* [DR94], uses the above observation to existentially quantify all variables from a CNF, one at a time. One way to implement the DP algorithm is using a mechanism known as *bucket elimination* [Dec97], which proceeds in two stages: *constructing and filling* a set of buckets, and then *processing* them in some order. Specifically, given a variable ordering π , we construct and fill buckets as follows:

- A *bucket* is constructed for each variable P and is *labeled* with variable P .
- Buckets are sorted top to bottom by their labels according to order π .
- Each clause α in the CNF is added to the first Bucket P from the top, such that variable P appears in clause α .

$$\Delta = \{ \{\neg A, B\}, \{\neg A, C\}, \{\neg B, D\}, \{\neg C, \neg D\}, \{A, \neg C, E\} \},$$

and the variable order C, B, A, D, E . Constructing and filling buckets leads to:³

$$C : \{\neg A, C\}, \{\neg C, \neg D\}, \{A, \neg C, E\}$$

$$B : \{\neg A, B\}, \{\neg B, D\}$$

$$A :$$

$$D :$$

$$E :$$

DP (continued)

to Bucket A :

$C : \{\neg A, C\}, \{\neg C, \neg D\}, \{A, \neg C, E\}$

$B : \{\neg A, B\}, \{\neg B, D\}$

$A : \{\neg A, \neg D\}$

$D :$

$E :$

The buckets below Bucket C will now contain the result of existentially quantifying variable C . Processing Bucket B adds one B -resolvent to Bucket A :

$C : \{\neg A, C\}, \{\neg C, \neg D\}, \{A, \neg C, E\}$

$B : \{\neg A, B\}, \{\neg B, D\}$

$A : \{\neg A, \neg D\}, \{\neg A, D\}$

$D :$

$E :$




Figure 3.3. A search tree for enumerating all truth assignments over variables *A*, *B* and *C*.

Look-ahead for sat: DPLL

(Davis-Putnam, Logeman and Laveland, 1962)

DPLL(φ)

Input: A cnf theory φ

Output: A decision of whether φ is satisfiable.

1. Unit_propagate(φ);
2. If the empty clause is generated, return(*false*);
3. Else, if all variables are assigned, return(*true*);
4. Else
5. Q = some unassigned variable;
6. return(DPLL($\varphi \wedge Q$) \vee
 DPLL($\varphi \wedge \neg Q$))

Figure 5.13: The DPLL Procedure

Boolean constraint propagation

Procedure UNIT-PROPAGATION

Input: A cnf theory, φ , $d = Q_1, \dots, Q_n$.

Output: An equivalent theory such that every unit clause does not appear in any non-unit clause.

1. queue = all unit clauses.
2. **while** queue is not empty, do.
3. $T \leftarrow$ next unit clause from Queue.
4. **for** every clause β containing T or $\neg T$
5. **if** β contains T delete β (subsumption elimination)
6. **else**, For each clause $\gamma = \text{resolve}(\beta, T)$.
 if γ , the resolvent, is empty, the theory is unsatisfiable.
7. **else**, add the resolvent γ to the theory and delete β .
 if γ is a unit clause, add to Queue.
8. **endfor**.
9. **endwhile**.

Theorem 3.6.1 *Algorithm* UNIT-PROPAGATION *has a linear time complexity.*

Example of DPLL




Figure 5.14: A backtracking search tree along the variables A, B, D, C for a cnf theory $\varphi = \{(\neg A \vee B), (\neg C \vee A), (A \vee B \vee D), C\}$. Hollow nodes and bars in the search tree represent illegal states, triangles represent solutions. The enclosed area corresponds to DPLL with unit-propagation.

Using Conditioned CNF at each node




Figure 3.5. A termination tree, where each node is labelled by the corresponding CNF. The last node visited during the search is labelled with $\{\}$. The label \times indicates the detection of a contradiction at the corresponding node.

Reduction from CSP to SAT

Example: CSP into SAT

Notation: variable-value pair = **vvp**

- vvp \rightarrow term
 - $V_1 = \{a, b, c, d\}$ yields $x_1 = (V_1, a)$, $x_2 = (V_1, b)$, $x_3 = (V_1, c)$, $x_4 = (V_1, d)$,
 - $V_2 = \{a, b, c\}$ yields $x_5 = (V_2, a)$, $x_6 = (V_2, b)$, $x_7 = (V_2, c)$.
- The vvp's of a variable \rightarrow disjunction of terms
 - $V_1 = \{a, b, c, d\}$ yields $x_1 \vee x_2 \vee x_3 \vee x_4$
- (How do we express: "At most one VVP per variable ")

$$\begin{aligned} & (x_1 \wedge \neg x_2 \wedge \neg x_3 \wedge \neg x_4) \vee (\neg x_1 \wedge x_2 \wedge \neg x_3 \wedge \neg x_4) \vee \\ & (\neg x_1 \wedge \neg x_2 \wedge x_3 \wedge \neg x_4) \vee (\neg x_1 \wedge \neg x_2 \wedge \neg x_3 \wedge x_4) \end{aligned}$$

Reduction from CSP to SAT

Example: CSP into SAT

Notation: variable-value pair = **vvp**

- vvp \rightarrow term
 - $V_1 = \{a, b, c, d\}$ yields $x_1 = (V_1, a)$, $x_2 = (V_1, b)$, $x_3 = (V_1, c)$, $x_4 = (V_1, d)$,
 - $V_2 = \{a, b, c\}$ yields $x_5 = (V_2, a)$, $x_6 = (V_2, b)$, $x_7 = (V_2, c)$.
- The vvp's of a variable \rightarrow disjunction of terms
 - $V_1 = \{a, b, c, d\}$ yields $x_1 \vee x_2 \vee x_3 \vee x_4$
- (How do we express: "At most one VVP per variable ")

$$\begin{aligned} & (x_1 \wedge \neg x_2 \wedge \neg x_3 \wedge \neg x_4) \vee (\neg x_1 \wedge x_2 \wedge \neg x_3 \wedge \neg x_4) \vee \\ & (\neg x_1 \wedge \neg x_2 \wedge x_3 \wedge \neg x_4) \vee (\neg x_1 \wedge \neg x_2 \wedge \neg x_3 \wedge x_4) \end{aligned}$$

CSP into SAT (cont.)

Constraint: $C_{V_1V_2} = \{(a, a), (a, b), (b, c), (c, b), (d, a)\}$

1. Way 1: Each inconsistent tuple \rightarrow one disjunctive clause

- For example: $\neg x_1 \vee \neg x_7$ how many?

2. Way 2:

a) Consistent tuple \rightarrow conjunction of terms $x_1 \wedge x_5$

b) Each constraint \rightarrow disjunction of these conjunctions

$$\begin{aligned} & (x_1 \wedge x_5) \vee (x_1 \wedge x_6) \vee (x_2 \wedge x_7) \\ & \vee (x_3 \wedge x_6) \vee (x_4 \wedge x_5) \end{aligned}$$

\rightarrow transform into conjunctive normal form (CNF)

Question: find a truth assignment of the Boolean variables such that the sentence is satisfied

Outline

- The search tree for CSPs, Variable ordering and consistency level
- Look-ahead for value selection:
 - Forward checking,
 - Full-arc-consistency,
 - partial look-ahead,
 - maintaining arc-consistency
- Dynamic Variable ordering (DVO, DVFC)
- Search for Satisfiability
- Converting a CSP into a SAT problem